


Industrial Use Laser

VLM-635/650-01G Series



FEATURES:


- Industrial Red Dot Laser.
- Glass aspherical lens for wide operating temperature range with APC Driver Circuit inside, ideal for industrial Laser application.
- This module has integrated optic, laser diode, and APC driver circuit.
- APC Driver Circuit enables the Laser output power safe and constant.
- Includes patented solid brass structure for the best shock resistance and better heat transfer consideration.
- Utilize Glass Lens, spot-size maintain tight-dot while temperature fluctuate between -20°C ~50°C.
- Dimensions : $\Phi 10.5 \times 18.4$ mm ($\Phi 0.413" \times 0.724"$)
- Wavelength : 635 / 650 nm
- Output power : Class II – less than 1mW / Class IIIa – less than 5mW.
- Beam Divergence (Half Angle) : 0.4 mRad
- 2.6~5 VDC operation.
- Connection type : Lead wire / Spring.

APPLICATIONS:

- Industrial Red Dot Laser – glass aspherical lens for wide operating temperature range. Ideal for Industrial positioning, measuring, pointing and laser sighting device.
- Wood processing.
- Metal processing.
- Stone processing.
- Textile industry.
- Food industry.
- Automotive industry.
- Medical science

VLM-635/650-01G Series

OUTLINE DIMENSIONS (UNITS: mm)



SPECIFICATIONS

SPECIFICATIONS		635-01G	650-01G
1	Dimensions	$\Phi 10.5 \times 18.4 \text{ mm}$ ($\Phi 0.413" \times 0.724"$)	
2	Operating voltage (Vop)	2.6~5 VDC	
3	Operating current (Iop)	< 50mA	< 35mA
4	Continuous wave output power (Po)	LPT<1mW / LPA \leq 2.5mW	
5	Wavelength at peak emission (λ_p)	630~645nm	645~665nm
6	Collimating lens	Aspherical Glass lens($\phi 6.35$)	
7	Spot size at 5M	4 \pm 1 mm	
8	Divergence (Half Angle)	0.4 mRad	
9	Operating temp. range	-20 $^{\circ}$ C ~+50 $^{\circ}$ C	
10	Storage temp. range	-20 $^{\circ}$ C ~+65 $^{\circ}$ C	
11	Housing	Brass	
12	Mean time to failure (MTTF) 25 $^{\circ}$ C	5000hrs	10000hrs

Note : Laser module housing is an electrical positive surface, it is imperative that contact between the laser module and the machine be avoided. This is to prevent damage from the machine electrical leakage. Surge protected power supply to the laser module is strongly recommended.

VLM-635/650-01G Series

ORDER CODE

Order Code	Wavelength	Output Power	Connection Type
VLM-635-01G LPA	635 nm	≤ 2.5mW	Lead Wire
VLM-635-01G LPT	635 nm	< 1mW	Lead Wire
VLM-635-01G SPA	635 nm	≤ 2.5mW	Spring
VLM-635-01G SPT	635 nm	< 1mW	Spring
VLM-650-01G LPA	650 nm	≤ 2.5mW	Lead Wire
VLM-650-01G LPT	650 nm	< 1mW	Lead Wire
VLM-650-01G SPA	650 nm	≤ 2.5mW	Spring
VLM-650-01G SPT	650 nm	< 1mW	Spring

SAFETY LABEL

